# can-am.

## **COMMANDER XT 1000R**

#### **HIGHLIGHTS**

**ENGINE** 

<ul> <li>Proven Rotax engine</li> <li>Dependable drivetrain</li> <li>Sport segment-worthy suspension</li> </ul>
Rugged taskmaster     Work-oriented functionality     Vehicle protection and rigidity
Interior focused on comfort Superior fit and finish Low cost of ownership
90.6 in. (230.1 cm) wheelbase 13 in. (33 cm) ground clearance 15 in. (38.1 cm) suspension travel 2,000 lb (907.2 kg) towing capacity Dynamic Power Steering (DPS™) Visco-Lok¹ QE front differential SPORT/ECO™ modes D.E.S.S. key with Start/Stop button Premium half doors Mudguards Rear differential with Turf mode
<ul> <li>64 in. (162.6 cm) wide with arched double A-arm</li> <li>28 in. XPS Trail King tyres</li> <li>14 in. cast-aluminum wheels</li> <li>XT front bumper</li> <li>4,500 lb (2,014 kg) winch</li> <li>Full roof</li> <li>7.6 in. digital display with keypad</li> <li>Can-Am LED signature</li> <li>Painted-color options</li> </ul>

Туре	100 hp, Rotax® 976 cc, V-twin, liquid-cooled
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	Quick Response System (QRS) CVT with high-airflow ventilation and Electronic Drive Belt Protection Extra-L/H/N/R/P
Drive Train	Selectable Turf Mode/2WD/4WD with Visco-Lok† QE auto-locking front differential
Driving Assistance	Electronic Hill Descent Control SPORT/ECO™ modes
Power Steering	Dynamic Power Steering (DPS)
SUSPENSIONS	
Front Suspension	Arched double A-arm with sway bar/15 in. (38.1 cm) travel
Front Shocks	Twin-tube gas-charged shocks
Rear Suspension	Arched TTA with sway bar/15 in. (38.1 cm) travel
Rear Shocks	Twin-tube gas-charged shocks
TYRES & WHEELS	
Front Tyres	XPS Trail King 28 x 9 x 14 in.
Rear Tyres	XPS Trail King 28 x 11 x 14 in.
Wheels	14 in. cast-aluminum
BRAKES	
Front	Dual 220 mm disc brakes with hydraulic twin-piston calipers
Rear	Dual 220 mm disc brakes with hydraulic twin-piston calipers

1000R



### Oxford Blue / 1000R

#### **DIMENSIONS & CAPACITIES**

Estimated Dry Weight	1,675 lb (759.8 kg)
Chassis/Cage	Profiled cage ROPS approved
LxWxH	130 x 64 x 74 in. (330.2 x 162.6 x 188.3 cm)
Wheelbase	90.6 in. (230.1 cm)
Ground Clearance	13 in. (33 cm)
Cargo Box Dimensions	29.5 x 45.2 x 10.6 in. (75.1 x 114.7 x 27 cm)
Cargo Box Capacity	600 lb (272.2 kg)
Towing Capacity	2,000 lb (907.2 kg)
Payload Capacity	1,030 lb (467.2 kg)
Storage Capacity	Total: 7.3 gal (27.6 L) Glove box: 4.1 gal (15.6 L) Driver storage: 0.4 gal (1.5 L) Center console and cup holders: 0.8 gal (3.1 L) Side cargo box storage (passenger side): 1.6 gal (5.9 L) Dual side panel storage: 0.8 gal (3.0 L)
Fuel Capacity	10 gal (38 L)
Gauge	
Instrumentation	Speedometer, tachometer, odometer, trips and hour meters,
	Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature
Instrumentation	Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature  Lighter-type DC outlet in console (10 A)  RF Digitally Encoded Security System (D.E.S.S.™)
Instrumentation Anti-Theft System	Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature  Lighter-type DC outlet in console (10 A)  RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button  650 W
Instrumentation Anti-Theft System Magneto	Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature  Lighter-type DC outlet in console (10 A)  RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button  650 W  Two 55 W reflector headlights with unique Can-Am LED
Instrumentation Anti-Theft System Magneto Lighting	Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature  Lighter-type DC outlet in console (10 A)  RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button  650 W  Two 55 W reflector headlights with unique Can-Am LED signature and LED tail lights
Instrumentation Anti-Theft System Magneto Lighting Winch	Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature  Lighter-type DC outlet in console (10 A)  RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button  650 W  Two 55 W reflector headlights with unique Can-Am LED signature and LED tail lights  4,500 lb (2,041 kg) winch with roller fairlead
Instrumentation Anti-Theft System Magneto Lighting Winch Steering Wheel	Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature  Lighter-type DC outlet in console (10 A)  RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button  650 W  Two 55 W reflector headlights with unique Can-Am LED signature and LED tail lights  4,500 lb (2,041 kg) winch with roller fairlead  Adjustable tilt steering  Premium half doors Full skid plate Mudguards XT front bumper
Instrumentation Anti-Theft System Magneto Lighting Winch Steering Wheel Protection	Speedometer, tachometer, odometer, trips and hour meters, fuel, gear position, SPORT/ECO™ modes, seat belt and 4 x 4 indicator, rear diff lock indicators, diagnostics, clock, battery voltage, engine temperature  Lighter-type DC outlet in console (10 A)  RF Digitally Encoded Security System (D.E.S.S.™) with Start/Stop button  650 W  Two 55 W reflector headlights with unique Can-Am LED signature and LED tail lights  4,500 lb (2,041 kg) winch with roller fairlead  Adjustable tilt steering  Premium half doors Full skid plate Mudguards XT front bumper Full roof  2 in. hitch receiver

